

## CERTIFICATIONS



### SPECIFICATIONS

|              |                        |
|--------------|------------------------|
| Wattage      | 15W-25W                |
| Voltage      | 120V                   |
| Power Factor | >0.95                  |
| Dimmable     | Triac-Dimming 100%-10% |

### PHYSICAL

|                       |                               |
|-----------------------|-------------------------------|
| Operating Temperature | -20°C to 45°C (-4°F to 113°F) |
| Material              | Steel                         |
| Mounting              | Surface Mounted               |
| Lens                  | PC Diffuser                   |
| Finish                | Brush Nickel/Black            |
| Lighting              | LED                           |
| CCT                   | 3CCT:3000K/4000K/5000K        |
| CRI                   | 80+                           |

### PERFORMANCE

|                |                           |
|----------------|---------------------------|
| Warranty       | 3 years                   |
| Certifications | ETL, CETL File No.5017812 |
| IP Rating      | IP44, Damp Location       |
| LED Lifetime   | 35,000 hours              |

### NOTES

|          |        |
|----------|--------|
| Use only | Indoor |
|----------|--------|

## LED Round Flush Mount



### ENERGY CHART

| SIZE | LENGTH inches | WIDTH inches | HEIGHT inches | WATTAGE | LUMENS | EFFICACY lm/w |
|------|---------------|--------------|---------------|---------|--------|---------------|
| 10   | 10            | 10           | 3.4           | 15      | 1050   | 70            |
| 12   | 12            | 12           | 3.4           | 15      | 1050   | 70            |
| 14   | 14            | 14           | 3.9           | 22      | 1750   | 70            |
| 16   | 16            | 16           | 4.2           | 25      | 1750   | 70            |

### LED'S SPECTRUM WAVE FORM

#### SPECTRUM DISTRIBUTION

