USA ENERGY LLC

CERTIFICATIONS

ETL Intertek | FC | IC | 3-YEAR WARRANTY | IP44 RATED | DAMP LOCATION

LED Round Puff Flush Mount

SPECIFICATIONS

Wattage	15W
Voltage	120V
Power Factor	>0.95
Dimmable	Triac-Dimming 100%-10%

PHYSICAL

Operating Temperature	-20ºC to 45ºC (-4°F to 113°F)
Material	Steel
Mounting	Surface Mounted
Lens	PMMA Diffuser
Finish	Brushed Nickel/Black
Lighting	LED
CCT	3CCT:3000K/4000K/5000K
CRI	80+

PERFORMANCE

Warranty	3 years
Certifications	ETL, CETL File No.5017812
IP Rating	IP44，Damp Location
LED Lifetime	35,000 hours

NOTES

Use only	Indoor

PMMA Diffuser
High Transparency and Excellent Flexibility

Steel Pan
Delicate and Beautiful

ENERGY CHART

SIZE	LENGTH inches	WIDTH inches	HEIGHT inches	WATTAGE	LUMENS	EFFICACY lm/w
9	9	9	4.5	15	1050	70

LED'S SPECTRUM WAVE FORM

SPECTRUM DISTRIBUTION

色容差： 0.1 SDCM

x=0.459 y=0.412 ANSI/2700K